

||| PETROKING LT STYLE 3228

Exceptional performance and value.



RED WING SHOES® | PETROKING LT | DIRECT ATTACH CONSTRUCTION

3228 MEN'S 6-INCH BOOT



SPECS

- 01 – TREDMAX RUBBER OUTSOLE
Delivers exceptional slip resistance
- 02 – PREMIUM SAFETY TOE CAP
Lightweight, rugged nylon composite material meets EN ISO and ASTM standards
- 03 – FORCEGUARD™
Protects toe area from abrasion, oils and chemicals
- 04 – MADE IN ITALY

SPECIFICATIONS

Safety Features	Non-metallic Toe Electrical Hazard Puncture Resistant
Upper	Full Grain Brown Leather
Lining	3D Mesh Air Net
Insole	Q Flex TX T6
Shank	Nylon
Last	RW51423
Construction	Direct Attach
Ratings	EN ISO 20345:2011 SB SRC P E WRU HRO FO ASTM F2413-11, M/I/75/C/75, EH PR
EU Sizes	36,37,38,39,40,41,42,43,44,45,46,47,48
Origin	Made in Italy
Technology	ForceGuard™ Lenzi® ComfortGard
Outsole	TredMax



Slip	Best
Oil/Gas	Best
Chemicals	Best
Abrasions	Best
Heat	Best
Non-Marking	Yes



HEAT RESISTANT OUTSOLE
Designed and tested to perform on high heat surfaces.



SLIP RESISTANCE RATED
Meets SRC slip requirement.

