

## FEATURES

- 14500 Lumens for optimum brightness and visibility
- Cool white light
- Highly efficient light rating of A+ – greater than 90%
- IP65 rating. Dust tight & can withstand water spray from all directions.
- Beam angle: 120°C
- Working voltage of 85-260V
- LED Lifespan of 50,000 hours.
- Luminous efficiency of 80-90 lm/W
- Operating temperature of -40°C to +50°C
- Premium build materials of aluminium and toughened glass.

## RS PRO LED Floodlight, 3 LED, 150 W, 13500 → 14500lm, IP65 85 → 265 V

RS Stock No.: 872-4127



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

Our RS Pro floodlights are high powered LED lights that have a brilliant build quality. You can hang them from the wall or ceiling with our included mounting bracket. With a rating of IP65 they are suitable for indoor and outdoor use. Our LED Floodlights also have a brilliant efficiency rating of A+.

[872-4127](#): 150W, 13500-14500 lumens

[872-4136](#): 160W, 12800-14400 lumens

[872-4139](#): 200W, 16000-18000 lumens

## General Specifications

<b>Floodlight Type</b>	Outdoor
<b>Number of LEDs</b>	3
<b>Luminosity</b>	13500lm to 14500lm
<b>Lumen Efficiency</b>	>80lm/w to 90lm/w
<b>Light Colour</b>	Cool White
<b>Colour Temperature</b>	6500K
<b>Beam Angle</b>	120°
<b>Case Material</b>	Aluminium
<b>Housing Colour</b>	Black
<b>Applications</b>	Warehouses, Car Parks, Walkways, Construction areas, Parks and gardens, Home security

## Electrical Specifications

<b>Wattage</b>	150W
<b>Voltage</b>	85 → 265 V
<b>Frequency Range</b>	50Hz to 60Hz
<b>Lamp Type</b>	LED
<b>Solar Panel</b>	No
<b>Life Hours</b>	50000h
<b>Lamp's Efficiency (%)</b>	>90%

### Mechanical Specifications

<b>Dimensions</b>	190mm x 425mm x 325mm
<b>Height</b>	190mm
<b>Width</b>	425mm
<b>Depth</b>	325mm

### Operation Environment Specifications

<b>Operating Temperature Range</b>	-30°C to 60°C
<b>Minimum Operating Temperature</b>	-30°C
<b>Maximum Operating Temperature</b>	60°C

### Protection Category

<b>IP Rating</b>	IP65
------------------	------

### Approvals

<b>Compliance/Certifications</b>	EN61340
<b>Standards Met</b>	CE, DLC, FCC, RoHS Compliant, UL
<b>EU Energy Efficiency Rating</b>	A+





